



**SMOOTH SURFACE**



TEXTILE CARCASS		CONVEYING SURFACE		DRIVING SURFACE	
Material:	<b>POLYESTER</b>	Material:	<b>PU</b>	Material:	<b>FABRIC WITH TPU IMPREGNATION</b>
Number of plies:	<b>2</b>	Thickness:	<b>0,2 mm</b>	Thickness:	-
Fabric:	<b>RIGID</b>	Surface:	<b>SMOOTH</b>	Surface:	<b>FABRIC</b>
	<b>KNIFE EDGE</b>	Color:	<b>WHITE</b>	Color:	<b>WHITE</b>
		Hardness Shore A:	-	Hardness Shore A:	-
		(+/- 5)			

**TECHNICAL DATA SHEET**

BELT THICKNESS	WEIGHT KG/M2	WORKING LOAD AT 1% ELONGATION	MAX ADMISSIBLE PULL	MINIMUM PULLEY DIAMETER		WORKING TEMPERATURE °C	ANTISTATIC
				FLEXING	BACK FLEXING		
<b>1,3 mm</b>	<b>1,5</b>	<b>6 N/mm</b>	<b>12 N/mm</b>	<b>8 mm</b>	<b>16 mm</b>	<b>-20 / 100</b>	<b>YES</b>

**MOST POPULAR APPLICATION**



PACKAGING

PIZZA

DRIED PASTA

CHOCOLATE

SWEET AND SALTY SNACKS

BAKERY PRODUCTS

BREAD INDUSTRY