



**GP SUPER GRIP SURFACE**

TEXTILE CARCASS		CONVEYING SURFACE	DRIVING SURFACE	
Material:	<b>POLYESTER</b>	Material:	<b>PVC</b>	Material: <b>FABRIC WITH TPU IMPREGNATION</b>
Number of plies:	<b>2</b>	Thickness:	<b>1,7 mm</b>	Thickness: <b>-</b>
Fabric:	<b>RIGID</b>	Surface:	<b>GP SUPER GRIP</b>	Surface: <b>FABRIC</b>
		Color:	<b>DARK GREEN</b>	Color: <b>GREY</b>
		Hardness Shore A:	<b>45</b>	Hardness Shore A: <b>-</b>
		(+/- 5)		

**TECHNICAL DATA SHEET**

BELT THICKNESS	WEIGHT KG/M2	WORKING LOAD AT 1% ELONGATION	MAX ADMISSIBLE PULL	MINIMUM PULLEY DIAMETER		WORKING TEMPERATURE °C	ANTISTATIC
				FLEXING	BACK FLEXING		
<b>5,2 mm</b>	<b>3,7</b>	<b>8 N/mm</b>	<b>16 N/mm</b>	<b>50 mm</b>	<b>60 mm</b>	<b>-10 / 60</b>	<b>YES</b>

**MOST POPULAR APPLICATION**

